

MOTORIDUTTORI CON FINECORSA REGOLABILE A VITE
MOTORS WITH ADJUSTABLE SCREW END STROKE



Serie Ø55 V7

Articolo Item	Modello Model	Coppia Torque	Velocità Speed	Peso avvolgibile* Rolling shutter weight*		Potenza assorbita Absorbed power	Corrente assorbita Current consumption	Misura Dimension
				H=2,4m kg	H=3,0m kg			
		Nm	gir/min. rpm			W	A	C (mm)
570.M.N1.00	V7-80/12	80	12	116	102	375	1,70	640
570.M.N2.00	V7-100/12	100	12	146	127	410	1,85	640
570.M.N3.00	V7-130/9	130	9	189	166	410	1,85	640

* Portate indicative: vedi tabella pag. 12 per dettagli – * Indication of capacity: see table pag. 12 for details

Alimentazione Power supply	230Vac / 50Hz	
Tempo di funzionamento continuo Continuous operating time	4 min	
Grado di protezione Protection degree	IP 44	
Cavo di alimentazione Power input cable	4 x 0,75 mm ² - L=2,5m	
Classe di isolamento Insulation class	F	
Giri finecorsa Limit switch rotation	0 ÷ 28	
Marcatura Marking	CE	

